

TH 45 EX PUMP

Pumps range



3 YEARS
WARRANTY

2"
50 mm

DISCHARGE FLOW
42 m³/h

GASOLINE

With deeper impeller vanes coupled with a large volute discharge opening, our semi-trash pumps can pass murky water that contains small solid objects without clogging the passage. These self-priming construction pumps feature a tough, silicone-carbide mechanical seal. Semi-trash pumps are ideal for dewatering on construction and agricultural sites or in rental applications.

Serial equipment

- ✓ Self-priming
- ✓ Recoil start
- ✓ Silicon carbide mechanical seal
- ✓ Gasoline 4-stroke engine
- ✓ Oil sensor security
- ✓ Plastique strainer, hose coupling and band

Optional equipment

- + Wheelbarrow kit (factory option): REF. 13
- + Fire fighter hose coupling
- + Maintenance kit N°1

TH 45 EX

| | | |
|--------------------------------------|-------|----------------------|
| Pump type | | Self-Priming |
| Suction Ø coupling | mm | 50 (2") |
| Delivery Ø coupling | mm | 50 (2") |
| Discharge flow | L/min | 700 |
| Discharge flow | m³/h | 42 |
| Pressure | bar | 2.3 |
| Maximum total head | m | 23 |
| Discharge head | m | 8 |
| Solid size Ø (Ø of Hole of strainer) | mm | 20 |
| Mechanical seal | | Silicon carbide |
| Engine model | | WORMS EX16 |
| Engine type | | 4 stroke - OHC |
| Fuel type | | Unleaded gasoline 95 |
| Fuel tank capacity | L | 3.2 |
| Autonomy | h | 3 h |
| Dimensions L x W x H | mm | 527 x 368 x 417 |
| Packaging dimensions L x W x H | mm | 540 x 380 x 440 |
| Dry weight | kg | 26 |
| Gross weight | kg | 28 |

WORMS Entreprises

ZAC de Lamirault
39 rue de Lamirault
77090 Collégien
FRANCE
TEL +33 (0) 1 64 76 29 67
FAX +33 (0) 1 64 76 29 99
export@wormsentreprises.com
www.wormsentreprises.com