

## TH 63 EX PUMP

Pumps range



**3 YEARS**  
WARRANTY

3"  
75 mm

DISCHARGE FLOW  
60 m<sup>3</sup>/h

GASOLINE

With deeper impeller vanes coupled with a large volute discharge opening, our semi-trash pumps can pass murky water that contains small solid objects without clogging the passage. These self-priming construction pumps feature a tough, silicon-carbide mechanical seal. Semi-trash pumps are ideal for dewatering on construction and agricultural sites or in rental applications.

### Serial equipment

- ✓ Self-priming
- ✓ Recoil start
- ✓ Silicon carbide mechanical seal
- ✓ Gasoline 4-stroke engine
- ✓ Oil sensor security
- ✓ Plastique strainer, hose coupling and band

### Optional equipment

- + Wheelbarrow kit (factory option): REF. 13
- + Fire fighter hose coupling
- + Maintenance kit N°1

### TH 63 EX

Pump type		Self-Priming
Suction Ø coupling	mm	75 (3")
Delivery Ø coupling	mm	75 (3")
Discharge flow	L/min	1000
Discharge flow	m <sup>3</sup> /h	60
Pressure	bar	2.6
Maximum total head	m	26
Discharge head	m	8
Solid size Ø (Ø of Hole of strainer)	mm	20
Mechanical seal		Silicon carbide
Engine model		WORMS EX17
Engine type		4 stroke - OHC
Fuel type		Unleaded gasoline 95
Fuel tank capacity	L	3.2
Autonomy	h	2 h 20
Dimensions L x W x H	mm	527 x 368 x 417
Packaging dimensions L x W x H	mm	540 x 380 x 440
Dry weight	kg	27.5
Gross weight	kg	(29.5)

### WORMS Entreprises

ZAC de Lamirault  
39 rue de Lamirault  
77090 Collégien  
FRANCE  
TEL +33 (0) 1 64 76 29 67  
FAX +33 (0) 1 64 76 29 99  
export@wormsentreprises.com  
www.wormsentreprises.com