

TECHNICAL DATA

SINGLE DIRECTION VIBRATORY PLATES

BVP 18/45, BVP 18/45 D



Compact

Guide handle fully foldable



Robust and reliable

V-belt all around protected against damage



Safe transport

Transport handles (standard) and transport wheels (optional)

Shipping dimensions in m3

BVP 18/45 0,149


BVP 18/45 D 0,181

Standard Equipment

- ☒ Vibration insulated steering bow, foldable
- ☒ Detachable steering handle
- ☒ Highly wear resistant base plate
- ☒ Automatic shutdown at low oil level (BVP18/45)
- ☒ Recoil starter
- ☒ Single point lifting device
- ☒ Fully protected V-belt
- ☒ Carrying handles
- ☒ 3-2-1 Warranty
- ☒ Engine protection frame (BVP18/45D)
- ☒ Automatic decompression (BVP18/45D)

Optional Equipment

- ☐ Sprinkler system (+7kg)
- ☐ Transport wheels (+4kg)
- ☐ Plastic mat
- ☐ Tool kit
- ☐ Service Kit
- ☐ TOUGH WARRANTY
- ☐ Comfort guide handle
- ☐ Special painting
- ☐ Engine protection frame (BVP18/45)




Dimensions in mm

	H	H1	L	L1	W
BVP 18/45	535	915	1115	558	450
BVP 18/45 D	650	915	1115	558	450

Technical Data

		BOMAG BVP 18/45	BOMAG BVP 18/45 D
Weights			
Operating weight CECE	kg	91	104
Basic weight	kg	90	103
Dimensions			
Working width	mm	450	450
Driving Characteristics			
Working speed, max.	m/min	25	25
Max. gradeability (dep. on soil con.)	%	30	30
Drive			
Engine manufacturer		Honda	Hatz
Type		GX 160	1B20
Emission stage		StageV/CARB P.3	Stage V
Cooling		air	air
Number of cylinders		1	1
Performance SAE J 1349	kW	3,6	3,1
Speed	min-1	3.600	3.000
Drive system		mech.	mech.
Fuel		Gasoline	Diesel
Fuel comsump. aver. during operation	l/h	1,1	0,7
Exciter system			
Frequency	Hz	90	90
Centrifugal force	kN	18	18
Amplitude	mm	1,63	1,63
Capacities			
Fuel	l	3,1	3,0
Water	l	7,0	7,0

Technical modifications reserved. Machines may be shown with options.



PRE 834 12 010

040219 Sa04

BOMAG
Hellerwald
D-56154 Boppard
P.O. Box 5162
Tel. (0)6742 - 1000
Fax (0)6742 - 3090

